

**Productname :** KENNEDY AIR TOOL LUBRICANT  
**Ref.Nr.:** UDS000767\_3\_20161128 (EN)

**Creationdate :** 28.11.16 Version : 1.0  
**Replaces:**

**KENNEDY**  
QUALITY INDUSTRIAL TOOLING

## AIR TOOL LUBRICANT

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**KENNEDY AIR TOOL LUBRICANT**  
Bulk

Order Codes - KEN-732-8050K

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Kennedy Tools,  
Wigston,  
Leicester,  
England,  
LE18 2FS.  
Tel.: +44 (0) 116 288 8000  
Fax.: +44 (0) 116 288 8222

**Manufacturer** **CRC Industries UK Ltd.**  
**Ambersil House - Wylds Road**  
**Castlefield Industrial Estate**  
**TA6 4DD Bridgwater Somerset**  
**United Kingdom**  
**Tel.: +44 1278 727200**  
**Fax.: +44 1278 425644**  
**E-mail : hse.uk@crcind.com**

#### 1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

<b>Physical:</b>	Not classified
<b>Health:</b>	Not classified
<b>Environment:</b>	Not classified
<b>Other hazards :</b>	Repeated exposure may cause skin dryness or cracking.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No 1272/2008

<b>Precautionary statement(s):</b>	P102 : Keep out of reach of children. P501-2 : Dispose of contents/container to an authorised waste collection point.
<b>Supplemental Hazard</b>	Repeated exposure may cause skin dryness or cracking.

**Productname :** KENNEDY AIR TOOL LUBRICANT  
**Ref.Nr.:** UDS000767\_3\_20161128 (EN)

**Creationdate :** 28.11.16 Version : 1.0  
**Replaces:**



## AIR TOOL LUBRICANT

information:

### 2.3. Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Highly refined low mineral oils/hydrocarbons	-	-	-	50-100	Asp. Tox. 1	H304	
Highly refined base oil		-	-	1-10	-	-	

(\* Explanation phrases : see chapter 16)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>Contact with eyes :</b>	If substance has got into eyes, immediately wash out with plenty of water for several minutes Seek medical attention if irritation persists
<b>Contact with skin :</b>	Wash with water and soap. Seek medical attention if irritation persists
<b>Inhalation :</b>	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
<b>Ingestion :</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation :</b>	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
<b>Ingestion :</b>	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
<b>Skin contact :</b>	Repeated exposure may cause skin dryness or cracking. Symptoms : redness and pain
<b>Eye contact :</b>	Mildly irritating to eyes Symptoms : redness and pain

**Productname :** KENNEDY AIR TOOL LUBRICANT  
**Ref.Nr.:** UDS000767\_3\_20161128 (EN)

**Creationdate :** 28.11.16 Version : 1.0  
**Replaces:**

**KENNEDY**  
QUALITY INDUSTRIAL TOOLING

AIR TOOL LUBRICANT

#### 4.3. Indication of any immediate medical attention and special treatment needed

**General Advice :** If you feel unwell, seek medical advice (show the label where possible)  
If symptoms persist always call a doctor

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

water, foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

May form explosive vapour/air mixtures  
Forms hazardous decomposition products  
CO,CO2

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing including eye/face protection.

#### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

#### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

#### 6.4. Reference to other sections

For further information see section 8

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Keep away from heat and sources of ignition

**Productname :** KENNEDY AIR TOOL LUBRICANT  
**Ref.Nr.:** UDS000767\_3\_20161128 (EN)

**Creationdate :** 28.11.16 Version : 1.0  
**Replaces:**

**KENNEDY**  
 QUALITY INDUSTRIAL TOOLING

## AIR TOOL LUBRICANT

It is advisable to take precautions to avoid contact with skin and eyes when handling the product.  
 Ensure adequate ventilation  
 Avoid contact with skin and eyes.  
 Wash thoroughly after use  
 Wear protective gloves/protective clothing/eye protection/face protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place.  
 Keep out of reach of children.

### 7.3. Specific end use(s)

Lubricants

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
<b>National established exposure limits, United Kingdom</b>			
Highly refined base oil	-	TWA	5 mg/m3
		STEL	10 mg/m3

### 8.2. Exposure controls

<b>Control procedures :</b>	Ensure adequate ventilation Keep away from heat and sources of ignition
<b>Personal protection :</b>	Take precautions to avoid contact with skin and eyes when handling the product.
<b>inhalation :</b>	Ensure adequate ventilation In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equipped with organic gas/vapor cartridge (type A)
<b>hands and skin :</b>	Wear suitable protective gloves
Recommended gloves:	Nitrile
<b>eyes :</b>	Wear safety goggles according to EN 166.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Apperance : physical state :</b>	Liquid.
<b>colour :</b>	Yellow.
<b>odour :</b>	Oil.
<b>pH :</b>	Not applicable.

**Productname :** KENNEDY AIR TOOL LUBRICANT  
**Ref.Nr.:** UDS000767\_3\_20161128 (EN)

**Creationdate :** 28.11.16 Version : 1.0  
**Replaces:**

**KENNEDY**  
QUALITY INDUSTRIAL TOOLING

## AIR TOOL LUBRICANT

<b>Boiling point/range :</b>	> 200 °C
<b>Flash point :</b>	185 °C (Closed Cup)
<b>Evaporation rate :</b>	Not available.
<b>Explosion limits : upper limit :</b>	Not available.
<b>lower limit :</b>	Not available.
<b>Vapour pressure :</b>	Not available.
<b>Relative density :</b>	0.87 g/cm <sup>3</sup> (@ 15°C).
<b>Solubility in water :</b>	Insoluble in water
<b>Auto-ignition :</b>	Not available.
<b>Viscosity :</b>	20.6 cSt @ 40°C

### 9.2. Other information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

### 10.4. Conditions to avoid

Avoid overheating

### 10.5. Incompatible materials

Strong oxidising agent

### 10.6. Hazardous decomposition products

CO,CO<sub>2</sub>

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure:

**Inhalation :** Inhalation of solvent vapours may give rise to nausea, headaches and dizziness

**Productname :** KENNEDY AIR TOOL LUBRICANT  
**Ref.Nr.:** UDS000767\_3\_20161128 (EN)

**Creationdate :** 28.11.16 Version : 1.0  
**Replaces:**

**KENNEDY**  
QUALITY INDUSTRIAL TOOLING

## AIR TOOL LUBRICANT

**Ingestion :** After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.

**Skin contact :** Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis

**Eye contact :** May cause irritation.

### Toxicological data :

No information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Not classified

### Ecotoxicological data:

No information available

### 12.2. Persistence and degradability

No information available

### 12.3. Bioaccumulative potential

No information available

### 12.4. Mobility in soil

Insoluble in water

### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

No information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Product :** This material and its container must be disposed of in a safe way.  
Do not discharge into drains or the environment, dispose to an authorised

**Productname :** KENNEDY AIR TOOL LUBRICANT  
**Ref.Nr.:** UDS000767\_3\_20161128 (EN)

**Creationdate :** 28.11.16 Version : 1.0  
**Replaces:**

**KENNEDY**  
QUALITY INDUSTRIAL TOOLING

## AIR TOOL LUBRICANT

**National regulations :** waste collection point.  
Disposal should be in accordance with local, state or national legislation

### SECTION 14: Transport information

#### 14.1. UN number

UN-number : Not classified as hazardous for transport

#### 14.2. UN proper shipping name

Proper shipping name: Not applicable.

#### 14.3. Transport hazard class(es)

Class: Not applicable.  
ADR/RID - Classification code: Not applicable.

#### 14.4. Packing group

Packing group: Not applicable.

#### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No  
IMDG - Marine pollutant: No  
IATA/ICAO - Environmentally hazardous: No

#### 14.6. Special precautions for user

IMDG - Ems: Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.  
EU-directive 99/45/EC  
Regulation (EC) No 1272/2008 (CLP)  
Regulation (EC) No 1907/2006 (REACH)

**Productname :** KENNEDY AIR TOOL LUBRICANT  
**Ref.Nr.:** UDS000767\_3\_20161128 (EN)

**Creationdate :** 28.11.16 Version : 1.0  
**Replaces:**

**KENNEDY**  
QUALITY INDUSTRIAL TOOLING

AIR TOOL LUBRICANT

## 15.2. Chemical safety assessment

No information available

## SECTION 16: Other information

\*Explanation hazard statements: - : -

H304 : May be fatal if swallowed and enters airways.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission.