

## SAFETY DATA SHEET

### Line Marker 750ml - All Colours

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** Line Marker 750ml - All Colours    **Order code** KEN-734-6020K\_6040K\_6060K\_6080K\_6100K\_6140K\_6160K

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Linemarker Paint

##### 1.3. Details of the supplier of the safety data sheet

Supplier	Kennedy Tools Wigston Works Leicester England LE18 2FS	Manufacturer	Aztec Aerosols Gateway Crewe Cheshire CW1 6FA
	T+44 (0) 116 288 8000 F+44 (0) 116 288 8222		T+44 (0) 1270 656380 F+44 (0) 1270 656381 info@aztecaerosols.com

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0)7831 300868

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification

<b>Physical hazards</b>	Aerosol 1 - H222, H229
<b>Health hazards</b>	Eye Irrit. 2 - H319 STOT SE 3 - H336
<b>Environmental hazards</b>	Aquatic Chronic 3 - H412

**Classification (67/548/EEC or 1999/45/EC)** Xi;R36. F+;R12. R52/53,R66,R67.

**Human health** Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

**Environmental** The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See Section 12 for additional information on ecological hazards.

**Physicochemical** Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

##### 2.2. Label elements

###### Pictogram



**Signal word** Danger

## Line Marker 750ml - All Colours

<b>Hazard statements</b>	<p>H222 Extremely flammable aerosol.</p> <p>H229 Pressurised container: may burst if heated</p> <p>H319 Causes serious eye irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>
<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P102 Keep out of reach of children.</p> <p>P501 Dispose of contents/container in accordance with local regulations.</p> <p>P260 Do not breathe vapour/spray.</p> <p>P262 Do not get in eyes, on skin, or on clothing.</p>
<b>Contains</b>	ACETONE, AROMATIC HYDROCARBON, BUTYL ACETATE -norm

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>ACETONE</b>	<b>30-60%</b>
CAS number: 67-64-1	EC number: 200-662-2
	REACH registration number: 01-2119471330-49
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
<b>PROPANE</b>	<b>10-30%</b>
CAS number: 74-98-6	EC number: 200-827-9
	REACH registration number: Exempt under REACH
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Gas 1 - H220	F+;R12
Press. Gas	
<b>BUTANE</b>	<b>10-30%</b>
CAS number: 106-97-8	EC number: 203-448-7
	REACH registration number: Exempt under REACH
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Gas 1 - H220	F+;R12
Press. Gas	

## Line Marker 750ml - All Colours

<b>AROMATIC HYDROCARBON</b> <span style="float: right;"><b>5-10%</b></span>		
CAS number: 64742-95-6	EC number: 265-199-0	REACH registration number: 01-2119486773-24
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.	
<b>ISOBUTANE</b> <span style="float: right;"><b>5-10%</b></span>		
CAS number: 75-28-5	EC number: 200-857-2	REACH registration number: Exempt under REACH
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12	
<b>BUTYL ACETATE -norm</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 R66 R67	
<b>1,2,4-TRIMETHYLBENZENE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 95-63-6	EC number: 202-436-9	REACH registration number: 01-2119472135-42
<b>Classification</b> Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 Xn;R20 Xi;R36/37/38 N;R51/53	
<b>CUMENE</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 98-82-8	EC number: 202-704-5	REACH registration number: 01-2119473983-24
<b>Classification</b> Flam. Liq. 3 - H226 Asp. Tox. 1 - H304 STOT SE 3 - H335 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 Xn;R65 Xi;R37 N;R51/53	

**Line Marker 750ml - All Colours**

<b>MESITYLENE</b>		<b>&lt;1%</b>
CAS number: 108-67-8	EC number: 203-604-4	REACH registration number: 01-2119463878-19
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	R10 Xi;R37 N;R51/53	
STOT SE 3 - H335		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

<b>General information</b>	Move affected person to fresh air at once.
<b>Inhalation</b>	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes.

**4.2. Most important symptoms and effects, both acute and delayed****4.3. Indication of any immediate medical attention and special treatment needed****SECTION 5: Firefighting measures****5.1. Extinguishing media**

**Suitable extinguishing media** Extinguish with foam, carbon dioxide, dry powder or water fog.

**5.2. Special hazards arising from the substance or mixture**

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. The product is highly flammable. Forms explosive mixtures with air.

**5.3. Advice for firefighters**

**Protective actions during firefighting** Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.

**6.2. Environmental precautions**

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.

**6.3. Methods and material for containment and cleaning up**

## Line Marker 750ml - All Colours

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb spillage with non-combustible, absorbent material.

### 6.4. Reference to other sections

#### SECTION 7: Handling and storage

##### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Do not spray on a naked flame or any incandescent material. Eliminate all sources of ignition.

##### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

##### 7.3. Specific end use(s)

#### SECTION 8: Exposure Controls/personal protection

##### 8.1. Control parameters

###### Occupational exposure limits

###### ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

###### PROPANE

Long-term exposure limit (8-hour TWA): SUP ppm

Short-term exposure limit (15-minute): SUP ppm

###### BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm

Short-term exposure limit (15-minute): WEL 750 ppm

###### AROMATIC HYDROCARBON

Long-term exposure limit (8-hour TWA): SUP 600 mg/m<sup>3</sup>

###### ISOBUTANE

Long-term exposure limit (8-hour TWA): WEL 800 ppm

Short-term exposure limit (15-minute): WEL No std.

###### BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m<sup>3</sup>

###### 1,2,4-TRIMETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 25 ppm

###### CUMENE

Long-term exposure limit (8-hour TWA): WEL 25 ppm(Sk) 125 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 250 mg/m<sup>3</sup>(Sk)

###### MESITYLENE

Long-term exposure limit (8-hour TWA): WEL 25 ppm

WEL = Workplace Exposure Limit

## Line Marker 750ml - All Colours

**Ingredient comments** WEL = Workplace Exposure Limits WEL = Workplace Exposure Limits

### 8.2. Exposure controls

#### Protective equipment



**Appropriate engineering controls** Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

**Personal protection** When using do not smoke.

**Eye/face protection** Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

**Hand protection** Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material.

**Hygiene measures** Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

**Respiratory protection** If ventilation is inadequate, suitable respiratory protection must be worn.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Odour</b>	Organic solvents.
<b>Flash point</b>	< -40°C
<b>Upper/lower flammability or explosive limits</b>	Lower : 1.8% - Upper 9.5%
<b>Auto-ignition temperature</b>	410-580°C
<b>Comments</b>	Information given is applicable to the major ingredient.

#### 9.2. Other information

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

#### 10.2. Chemical stability

**Stability** Avoid the following conditions: Heat, sparks, flames.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

## Line Marker 750ml - All Colours

**Hazardous decomposition products** Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**General information** Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

**Inhalation** In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Eye contact** Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting. Repeated exposure may cause chronic eye irritation.

**Acute and chronic health hazards** Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

**Route of entry** Inhalation

**Target organs** Central nervous system Respiratory system, lungs

**Medical symptoms** Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness. Skin irritation.

### SECTION 12: Ecological Information

**Ecotoxicity** ENVIRONMENTAL HAZARDS: This product has not been tested but contains ingredients which are harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** Do not puncture or incinerate, even when empty.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

### SECTION 14: Transport information

## Line Marker 750ml - All Colours

### General

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

#### 14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID subsidiary risk	
ADR/RID label	2.1
IMDG class	2.1
IMDG subsidiary risk	
ICAO class/division	2.1
ICAO subsidiary risk	

#### Transport labels



#### 14.4. Packing group

Not applicable.

#### ADR/RID packing group

#### IMDG packing group

#### ICAO packing group

#### 14.5. Environmental hazards

##### Environmentally hazardous substance/marine pollutant

No.

#### 14.6. Special precautions for user

EmS F-D, S-U

#### Emergency Action Code



## Line Marker 750ml - All Colours

**Hazard Identification Number  
(ADR/RID)**

**Tunnel restriction code** (D)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

#### SECTION 15: Regulatory information

##### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
<b>EU legislation</b>	Commission Regulation (EU) No 453/2010 of 20 May 2010.
<b>Guidance</b>	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

##### 15.2. Chemical safety assessment

#### SECTION 16: Other information

<b>Revision date</b>	03/07/2015
<b>Revision</b>	2
<b>SDS number</b>	10970
<b>SDS status</b>	Approved.
<b>Risk phrases in full</b>	R10 Flammable. R11 Highly flammable. R12 Extremely flammable. R20 Harmful by inhalation. R36 Irritating to eyes. R36/37/38 Irritating to eyes, respiratory system and skin. R37 Irritating to respiratory system. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.

## Line Marker 750ml - All Colours

<b>Hazard statements in full</b>	H220 Extremely flammable gas.
	H222 Extremely flammable aerosol.
	H222 Extremely flammable aerosol.
	H225 Highly flammable liquid and vapour.
	H225 Highly flammable liquid and vapour.
	H226 Flammable liquid and vapour.
	H226 Flammable liquid and vapour.
	H229 Pressurised container: may burst if heated
	H229 Pressurised container: may burst if heated
	H304 May be fatal if swallowed and enters airways.
	H304 May be fatal if swallowed and enters airways.
	H315 Causes skin irritation.
	H315 Causes skin irritation.
	H319 Causes serious eye irritation.
	H319 Causes serious eye irritation.
	H335 May cause respiratory irritation.
	H335 May cause respiratory irritation.
	H336 May cause drowsiness or dizziness.
	H336 May cause drowsiness or dizziness.
	H411 Toxic to aquatic life with long lasting effects.
	H411 Toxic to aquatic life with long lasting effects.
	H412 Harmful to aquatic life with long lasting effects.
	H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.