
1. Identification:

Order Code: SOL-780-1950Q
 Commercial Name: Drywork Barrier Cream
 Other Names:
 Intended Use: Protect and moisturise.

Company: Solent, Osbourne Works, Leicester, England, LE18 1AT
 Tel: 0116 288 8000 Fax: 0116 288 8222
 Emergency Telephone Number: 0116 257 2445

2. Composition/Information on Ingredients:
Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Glycerol (Glycerol, mist)	1 - 10%	56-81-5		
Titanium dioxide (Titanium dioxide respirable)	0 - 0.5%	13463-67-7	236-675-5	

3. Hazards identification:

No significant hazard.

4. First aid measures:

Skin contact No irritation expected. Wash with water.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation May cause irritation to mucous membranes. Move the exposed person to fresh air.

Ingestion May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

5. Fire fighting Measures:

Extinguishing media Use extinguishing media appropriate to the surrounding fire conditions.

Fire hazards Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Wear suitable respiratory equipment when necessary.

6. Accidental release measures:

Personal precautions Ensure adequate ventilation of the working area.

Environmental precautions Do not allow product to enter drains. Prevent further spillage if safe.

Clean up methods Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. Handling & Storage:

Handling Adopt best Manual Handling considerations when handling, carrying and dispensing.

Storage Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. Exposure Control & Personal Protection:
Exposure limits

Glycerol	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 10
(Glycerol, mist)	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
Titanium dioxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 4
(Titanium dioxide respirable)	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
Titanium dioxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 10
(Titanium dioxide total inhalable)	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -

Engineering measures Ensure adequate ventilation of the working area.

Hand protection No precautions required to be mentioned.

Eye protection In case of splashing, wear: Approved safety goggles.

Protective equipment Adopt best manual considerations when handling, carrying and dispensing

9. Physical & Chemical properties:

Description	Viscous liquid.
Colour	White.
Odour	Pleasant.
pH	7.0

10. Stability & reactivity:

Stability Stable under normal conditions.

11. Toxicological information:

Toxicological information No known adverse health effects.

12. Ecological information:

Ecotoxicity No known adverse environmental effects.

13. Disposal considerations:

General information Dispose of in compliance with all local and national regulations.

14. Transport information:

Further information The product is not classified as dangerous for carriage.

15. Regulatory information:

Risk phrases NSH - No Significant Hazard.

16. OTHER INFORMATION:

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.